
### **Photopolymer Plate Processing Equipment**

3ES-WO50f Washout&Filter





#### 3ES-WO50f

Washout unit for processing photopolymer flexo plates up to a format size of 500 x 700 mm.

- The mechanical construction is designed with stainless steel frame robust easy to support and maintain.
- 7" Touch screen easily customize and setup for 20 different programs or LCD screen with 10 channels

#### Washout

Equipped with flat brush, rotating plate board, programmable temperature between 15°C to 65°C ( ±2°C ), thickness control and state of art filter which offers ecologically friendly and cost effective working.

- Suitable for any thickness of plates 0,7 mm to 7.0 mm
- Automatic plate thickness adjustment
- Automatic lid openin/closing
- Excellent permanent self-adhesive plate board for easy plate fixing/removing

State-of-art filter removes polymer residue in washing solution, the clean washing solution is recirculated to washout tank for reuse. The filter,

- keeps washout solution and tank clean
- extends life of the washing solution
- reduces maintance costs.








# **Photopolymer Plate Processing Equipment**

3ES-WO50f

Washout&Filter



## Technical Data

Product Name	3ES-WO50f
Maximum Plate Size	500 x 700 mm
Plate Type	Analog & Digital / Flexo /Water-wash
Washout Tank Capacity	71 liters
<b>Environmental Requirements</b>	Temperature: 15°C to 30°C Humidity: 40% -60%
Exhaust (Light Finisher)	NA
Compressed Air	Ø8 mm pipe connection/6 bar minimum
Nominal Power	3kW
Nominal Current	6A 400 V AC (3 Ph/N/PE)50/60 Hz
Dimension	1250*1020*1180 mm
Crate Dimension (approx.)	1350*1120*1330 mm
Weight	135 kg net / 195 kg gross



For all other information's or request please contact Mega.....

Mega Elektromekanik Mak. Iml. Ith. Ihr. San. Tic. Ltd. Sti.
Dudullu OSB DES-113 Sk. C-13 Blok N:58 34776 Umraniye Istanbul Turkey
T. +90 216 612 48 97 - 98 F. +90 216 612 15 72 info@3esmega.com





www.3esmega.com

